

<b>400-600A Digital Clamp Meters</b>		
<b>PR-202A</b>		
<b>Specification</b>		
Model		PR-202A
AC Current (A)	2A/20A/200A/400A 20A/200A/600A	±(1.5%+5)
AC Voltage (V)	2V/20V/200V/600V	±(1.2%+5)
DC Voltage (V)	200mV/2V/20V/200V/600V	±(0.8%+1)
Resistance (Ω)	200Ω/2KΩ/20KΩ/200KΩ/2MΩ/20MΩ	±(0.8%+3)
Temperature (°C)	-40°C ~ 1000°C	
Temperature (°F)	-40°F ~ 1832°F	
<b>Features</b>		
Display Count		1999
Auto Range		
Manual Range		√
Jaw Capacity		28mm
Diode		√
Auto Power Off		
Continuity Buzzer		√
Low Battery Indication		√
Data Hold		√
MAX Mode		√
MIN Mode		√
Full Icon Display		
Input Impedance for DCV	Around 10MΩ	√
<b>General Characteristic</b>		
Power	<b>PR-202A-9V Battery (6F22)</b>	
LCD Size	35.6mm X 18 mm	
Product Color	Red and Grey	
Product Net Weight	220g	
Product Size	210mm X 75.6mm X30 mm	
Standard Accessories	<b>PR-202A-Batteries, Test Lead,Carrying Bag</b>	
Standard Individual Packing	Gift Box, English Manual	
Standard Quantity Per Carton	40 PCs	
Standard Carton Measurement	540mm X 495mm X 335mm (0.09 CBM Per Standard Carton)	
Standard Carton Gross Weight	23Kg	